

angle of transoms
74° degrees

ALUMACRAFT®

2011 MODELS




CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE

BETTER BUILT

Can a boat be tough but agile? Strong but light on its feet?

It can if it's an Alumacraft.

Full-length double plating means twice the strength and protection all the way to the transom—without compromising agility. Compare our twin-plated 2XB Hull models against competing boats with twin-plating in the bow only.




One-piece, single sheet aluminum finely cut and shaped for greatest possible inherent strength




Top quality aluminum hulls with larger aircraft grade rivets for longevity



Durable wood-free heavy gauge aluminum seating and stringers



Twin plated 2XB hulls provide superior strength




A sustainable and larger, one-piece, hardened heavy-duty keel



Full-length, oversized spray rails for a drier ride in rough water



Water tested hulls ensure rivet and weld integrity




Gas-resistant expansion foam increases buoyancy and quiets the ride




Convenient wood-free storage and livewell compartment hatches



Highest quality marine grade plywood and carpeted decks



Automotive-grade base/clear coat paint with top quality graphics



Quality fit and finish from bow to stern for practicality and appeal

CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE



NEW RECESSED CONTROLS



NEW OPTIONAL BOW STORAGE LOCKER



REAR JUMP SEATS



CONSOLE W/ OPTIONAL GPS GRAPH



REAR LIVEWELL

"What I love about my Trophy is that it's a serious fishing boat or a serious family boat, depends on the day. There's plenty of storage for the whole family, and now with the optional bow rod storage and 2 large livewells, it's also my tournament boat. The ride? Well it's one of the reasons I chose Alumacraft over the competition."



TROPHY 175

	205	195	185	175
LENGTH	20' 8" (6.2m)	19' 8" (5.9m)	18' 8" (5.6m)	17' 8" (5.3m)
WIDTH: Maximum beam	98" (2.4 m)	98" (2.4 m)	98" (2.4 m)	94" (2.4 m)
DEPTH: Maximum/to floor	47"/27" (1.2 m/.69 m)	47"/27" (1.2 m/.69 m)	47"/27" (1.2 m/.69 m)	43"/25" (1.1 m/.64 m)
TRANSOM: Width/height	96"/25" (2.45 m/.64)	96"/25" (2.45 m/.64)	96"/25" (2.45 m/.64)	94"/25" (2.45 m/.64)
HORSEPOWER: Maximum	225 hp (167 kw)	200 hp (149 kw)	175 hp (130 kw)	150 hp (112 kw)
CAPACITY: Max Persons	9/2350 lbs (9/1066kg)	8/2000 lbs (8/907kg)	8/1760 lbs (8/798kg)	7/1600 lbs (7/725kg)
WEIGHT	1915 lbs (868 kg)	1805 lbs (818 kg)	1780 lbs (807 kg)	1550 lbs (703 kg)
FUEL TANK	50 gal (189 L)	38 gal (144 L)	38 gal (144 L)	38 gal (144 L)
HULL THICKNESS: Bottom/side	.100"/.080" (2.5 mm/2.0 mm)	.100"/.080" (2.5 mm/2.0 mm)	.100"/.080" (2.5 mm/2.0 mm)	.080"/.080" (2.0 mm/2.0 mm)
2XB BOW - 2nd plate	.100" (2.5mm)	.100" (2.5mm)	.100" (2.5mm)	.080" (2.0mm)
2XB AFT BOTTOM - 2nd plate	.100" (2.5mm)	.100" (2.5mm)	.100" (2.5mm)	.080" (2.0mm)
SEATS *	4	4	3	3
JUMP SEATS	2	2	2	2
PEDESTALS/ SOCKETS	5/6	5/6	4/5	4/5
BOW LIVE WELL **	22 gal (83.3L)	22 gal (83.3L)	22 gal (83.3L)	22 gal (83.3L)
AFT LIVE WELL ***	21 gal (71L)	21 gal (71L)	21 gal (71L)	21 gal (71L)
STEERING:	Hydraulic	Hydraulic	Hydraulic	Hydraulic


CONSOLE: With tilt wheel, walk-thru, tempered windshield, passenger console
INSTRUMENTATION: speedometer, tachometer, voltmeter, fuel gauge, horn, blank
STEREO: AM/FM/CD with 2 speakers, Sirius ready

* Driver's is stationary w/ slider, height adjust (Power height in 205, 195, 185)

** Aerated, bow insulated, bait systems, timers, light, remote drain (20" w x 10.5" h x 31.5" L / 55.9 cm x 26.7 cm x 80 cm)

*** Aerated, bow insulated, bait systems, timers, light, remote drain (13" w x 11" h x 36" L / 33 cm x 27.9 cm x 91.4 cm)

CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE



BOW ROD STORAGE



PORT ROD STORAGE



CONSOLE WITH OPTIONAL GPS GRAPH



REAR PRO LIVEWELL



STORAGE/ROD LOCKER

"This is the boat that I have been waiting for, great proven performance, loads of storage, dual tournament-size livewells, bow rod storage, and dual side rod storage. I found it to be the best value in it's class. My search is finally over!"



COMPETITOR 175 SPORT

	175 SPORT	175 CS	175 TILLER
LENGTH	17' 8" (5.38 m)	17' 8" (5.38 m)	17' 8" (5.38 m)
WIDTH: Maximum beam	95" (2.41 m)	95" (2.41 m)	95" (2.41 m)
DEPTH: Maximum to floor	43"/23" (1.09 m/.58 m)	43"/23" (1.09 m/.58 m)	43"/23" (1.09 m/.58 m)
TRANSOM: Width/height	93"/25" (2.36 m/.63 m)	93"/25" (2.36 m/.63 m)	93"/20" (2.36 m/.508 m)
HORSEPOWER: Maximum	150 hp (112 kw)	150 hp (112 kw)	75 hp (56 kw)
CAPACITY: Max Persons/Weight	5/1370 lbs (5/621 kg)	5/1370 lbs (5/621 kg)	5/1300 lbs (5/589 kg)
WEIGHT	1375 lbs (624 kg)	1285 lbs (583 kg)	1160 lbs (526 kg)
FUEL TANK	38 gal. (114 L)	38 gal. (114 L)	38 gal. (114 L)
HULL THICKNESS: Bottom/side	.080"/.080" (2.0 mm/2.0 mm)	.080"/.080" (2.0 mm/2.0 mm)	.080"/.080" (2.0 mm/2.0 mm)
2XB BOW - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)
2XB AFT BOTTOM - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)
SEATS *	2	2	2
PEDESTALS / SOCKETS	2/6	2/6	2/4
BOW LIVE WELL **	22 gal. (83.3 L)	22 gal. (83.3 L)	22 gal. (83.3 L)
AFT LIVE WELL ***	21 gal. (71 L)	21 gal. (71 L)	21 gal. (71 L)
STEERING:	hydraulic	hydraulic	N/A
INSTRUMENTATION: speedometer, tachometer, voltmeter, fuel gauge, horn, blank			

* Driver's is stationary w/ slider, height adjust

** Aerated, bait systems, light, remote drains (20" w x 10.5" h x 31.5" L / 55.9 cm x 26.7 cm x 80 cm)

*** Aerated, bait systems, light, remote drains (13" w x 11" h x 36" L / 33 cm x 27.9 cm x 91.4 cm)

CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE

"The new 185 has the size and features I need whether I'm fishing the big lake or just spending time on the water with the family. One reason I chose the Dominator is the layout—the rear jump seats, dual livewells and wide beam. It fishes very comfortably."

BOW ROD STORAGE

CONSOLE WITH OPTIONAL GPS GRAPH

REAR LIVEWELL

NEW TOP LOAD ROD STORAGE

NEW STARBOARD RECESSED CONTROLS



DOMINATOR 175 CS



DOMINATOR 165 SPORT

	185 SPORT	185 CS	175 SPORT	175 CS	165 SPORT	165 CS
LENGTH	18' 9" (5.71 m)	18' 9" (5.71 m)	17' 9" (5.4 m)	17' 9" (5.4 m)	16' 8" (5.0 m)	16' 8" (5.0 m)
WIDTH: Maximum beam	94" (2.38 m)	94" (2.38 m)	94" (2.38 m)	94" (2.38 m)	91" (2.31 m)	91" (2.31 m)
DEPTH: Maximum to floor	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	42" / 22" (1.06 m / .56 m)	42" / 22" (1.06 m / .56 m)
TRANSOM: Width/height	94" / 25" (2.39 m / .63 m)	94" / 25" (2.39 m / .63 m)	94" / 25" (2.39 m / .63 m)	94" / 25" (2.39 m / .63 m)	91" / 20" (2.31 m / .51 m)	91" / 20" (2.31 m / .51 m)
HORSEPOWER: Maximum	150 hp (130 kw)	150 hp (130 kw)	150 hp (111 kw)	150 hp (111 kw)	90 hp (67 kw)	90 hp (67 kw)
CAPACITY: Max Persons/Weight	6 / 1600 lbs (6 / 726 kg)	6 / 1600 lbs (6 / 726 kg)	6 / 1370 lbs (6 / 621 kg)	6 / 1370 lbs (6 / 621 kg)	5 / 1100 lbs (5 / 499 kg)	5 / 1100 lbs (5 / 499 kg)
WEIGHT	1530 lbs (694 kg)	1438 lbs (652 kg)	1482 lbs (672 kg)	1390 lbs (630 kg)	1250 lbs (567 kg)	1175 lbs (533 kg)
FUEL TANK	38 gal. (144 L)	38 gal. (144 L)	38 gal. (144 L)	38 gal. (144 L)	20 gal. (76 L)	20 gal. (76 L)
HULL THICKNESS: Bottom/side	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)
2XB BOW - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	N/A	N/A
2XB AFT BOTTOM - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	N/A	N/A
SEATS *	3	3	2	2	2	2
JUMP SEATS	2	2	2	2	2	2
PEDESTALS / SOCKETS	2/6	2/6	2/6	2/6	2/6	2/6
BOW LIVE WELL **	22 gal. (83.3 L)	22 gal. (83.3 L)	22 gal. (83.3 L)	22 gal. (83.3 L)	22 gal. (83.3 L)	22 gal. (83.3 L)
AFT LIVE WELL ***	13 gal. (49.2 L)	13 gal. (49.2 L)	13 gal. (49.2 L)	13 gal. (49.2 L)	13 gal. (49.2 L)	13 gal. (49.2 L)
STEERING:	hydraulic	hydraulic	hydraulic	hydraulic	No Feedback	No Feedback
INSTRUMENTATION: speedometer, tachometer, voltmeter, fuel gauge, horn, blank						

* Driver's is stationary w/ slider, height adjust

** Aerated, bait systems, light, remote drain bow only (20" w x 10.5" h x 31.5" L / 55.9 cm x 26.7 cm x 80 cm)

*** Aerated, bow insulated, bait systems, timers, light, remote drain (12" w x 9" h x 30" L / 30.48 cm x 22.86 cm x 76.2 cm)

Celebrating a 65 year tradition of excellence

DOMINATOR SERIES

165, 175 & 185

NEW FOR 2011



DOMINATOR 185 SPORT

Boat may be shown with optional equipment. See your dealer


STANDARD FEATURES

Hydraulic Steering, Lockable Rod Storage (Minimum Of 13 Rods Up To 7.5' On 175 And 185, 7' On 165), Lockable Glove Box Sport, Dual Livewells, Lockable 22 Gal: Dry Storage/ Ice Chest (185, 175), Battery Storage (3 Batteries), Electrical Circuit Breakers, Trolling Systems—12/24V Bow Outlet, Stowable Running Lights, Interior Courtesy Lights, Livewell Lights, 1 Manual Bilge Pump, Fire Extinguisher, Grab Handles


OPTIONAL EQUIPMENT

Trolling Motor, Graph (Minn Kota, Lowrance, Humminbird), Dual Bubble Windshield (Sports Only), Vinyl Floor, Stereo, Extra Seat, Mooring, Snap Covers

COLOR OPTIONS




Olympic White



Mica Black




Pacific Blue




Victory Red


■ STORAGE ■ ROD STORAGE ■ DRY STORAGE ■ LIVWELL ■ BATTERY STORAGE ● 12/24V OUTLET



185 Sport




185 CS




175 Sport



175 CS



165 Sport




165 CS




CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE

"I chose the Navigator 175 because it had everything I wanted in a high-performance fishing boat. An open layout, two big rod lockers, two livewells—including one oversized—and plenty of storage for stashing my gear."



SIDE ROD STORAGE



CONSOLE WITH OPTIONAL GPS GRAPH



BOW LIVEWELL




SIDE STORAGE



REAR PRO LIVEWELL
[175 SPORT, CS AND TILLER]



NAVIGATOR 165 CS



NAVIGATOR 165 TILLER



NAVIGATOR

	175 SPORT	175 CS	175 CC	175 TILLER	165 SPORT	165 CS	165 TILLER
LENGTH	17' 8" (5.38 m)	17' 8" (5.38 m)	17' 8" (5.38 m)	17' 8" (5.38 m)	16' 8" (5.08 m)	16' 8" (5.08 m)	16' 8" (5.08 m)
WIDTH: Maximum beam	95" (2.41 m)	95" (2.41 m)	95" (2.41 m)	95" (2.41 m)	91" (2.31 m)	91" (2.31 m)	91" (2.31 m)
DEPTH: Maximum to floor	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	43" / 23" (1.09 m / .58 m)	42" / 23" (1.06 m / .58 m)	42" / 23" (1.06 m / .58 m)	42" / 23" (1.06 m / .58 m)
TRANSOM: Width/height	93" / 25" (2.36 m / .63 m)	93" / 25" (2.36 m / .63 m)	93" / 20" (2.36 m / .51 m)	93" / 20" (2.36 m / .51 m)	90" / 20" (2.29 m / .51 m)	90" / 20" (2.29 m / .51 m)	90" / 20" (2.29 m / .51 m)
HORSEPOWER: Maximum	150 hp (112 kw)	150 hp (112 kw)	140 hp (104 kw)	75hp (56 kw)	90 hp (67 kw)	90 hp (67 kw)	75hp (56 kw)
CAPACITY: Max Persons	5/1370 lbs (5/621 kg)	5/1370 lbs (5/621 kg)	5/1370 lbs (5/621 kg)	5/1300 lbs (5/589 kg)	5/1340 lbs (5/608 kg)	5/1340 lbs (5/608 kg)	5/1245 lbs (5/565 kg)
WEIGHT	1357 lbs (616 kg)	1270 lbs (576 kg)	1196 lbs (542 kg)	1145 lbs (519 kg)	1050 lbs (476 kg)	965 lbs (438 kg)	925 lbs (420 kg)
FUEL TANK	38 gal (144 L)	38 gal (144 L)	38 gal (144 L)	38 gal (144 L)	20 gal (76 L)	20 gal (76 L)	20 gal (76 L)
HULL THICKNESS: Bottom/side	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)	.080" / .080" (2.0 mm / 2.0 mm)
2XB BOW - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	N/A	N/A	N/A
2XB AFT BOTTOM - 2nd plate	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	.080" (2.0 mm)	N/A	N/A	N/A
SEATS *	2	2	2	2	2	2	2
PEDESTALS / SOCKETS	2/6	2/6	0/2	2/4	2/6	2/6	2/4
BOW LIVE WELL **	34 gal. (128.7 L)	34 gal. (128.7 L)	N/A	34 gal. (128.7 L)	34 gal. (128.7 L)	34 gal. (128.7 L)	34 gal. (128.7 L)
AFT LIVE WELL ***	21 gal (71L)	21 gal (71L)	15 gal (56.8L)	21 gal (71L)	N/A	N/A	N/A
STEERING:	Hydraulic	Hydraulic	No Feedback	N/A	No Feedback	No Feedback	N/A
INSTRUMENTATION: speedometer, tachometer, voltmeter, fuel gauge, horn, blank							

* Driver's is stationary w/ slider, height adjust (Driver's NEPTUNE III Leaning post - 175 CC ONLY)
** Aerated, bait systems, light, remote drain - Bow only (12" w x 14" h x 54" L / 55.9 cm x 26.7 cm x 80 cm)
*** 175 models ONLY (13" w x 11" h x 36" L / 33 cm x 27.9 cm x 91.4 cm)
175 CC livewell located under console seat

Celebrating a 65 year tradition of excellence

NAVIGATOR SERIES

165 & 175



NAVIGATOR 175 SPORT

Boat may be shown with optional equipment. See your dealer


STANDARD FEATURES

Hydraulic Steering (175 Cs And Sport) Lockable Rod Storage (Minimum Of 10 Rods Up To 7.5'). Dual Livewells (175 Sport, Cs And Tiller), Bow Livewell (165S), Console Livewell (175 Cc), Lockable Glove Box (Sport Only), Battery Storage (3 Batteries), Electrical Circuit Breakers, Trolling Systems—12/24V Bow Outlet (Stern Tillers), Stowable Running Lights, Interior Courtesy Lights, Livewell Lights, 1 Manual Bilge Pump, Fire Extinguisher, Grab Handles


OPTIONAL EQUIPMENT

Trolling Motor, Graph (Minn Kota, Lowrance, Humminbird), Dual Bubble Windshield (Sports Only), Vinyl Floor, Stereo, Extra Seat, Mooring

COLOR OPTIONS



Olympic White



Mica Black




Pacific Blue




Victory Red


■ STORAGE ■ ROD STORAGE ■ LIVEWELL ■ BATTERY STORAGE ● 12/24v OUTLET




175 Sport




175 CS




175 CC




175 Tiller



165 Sport



165 CS



165 Tiller

MERCURY
Outboards

CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE



SIDE ROD STORAGE




BOW STORAGE



PRO STYLE BOW LIVEWELL



CONSOLE



SIDE/ROD STORAGE

"I had already heard about the Classic Series from other people, so when it came time to buy, the choice was pretty easy. The standard equipment, storage, open floor plan, and just the way it looks and handles on the water—I can see why they call it a Classic."



CLASSIC 165 TILLER

	CLASSIC 165 CS	CLASSIC 165 TILLER
LENGTH	16' 4" (5.0 m)	16' 4" (5.0 m)
WIDTH: Maximum beam	82" (2.1 m)	82" (2.1 m)
DEPTH: Maximum/to floor	35"/21" (.89 m/.53 m)	35"/21" (.89 m/.53 m)
TRANSOM: Width/height	82"/20" (2.1 m/.51 m)	82"/20" (2.1 m/.51 m)
HORSEPOWER: Maximum	75 hp (56 kw)	50 hp (37 kw)
CAPACITY: Max Persons	5/1280 lbs (5/580 kg)	5/1295 lbs (5/587 kg)
WEIGHT:	895 lbs (406 kg)	805 lbs (365 kg)
FUEL TANK:	20 gal. (75.7 L)	20 gal. (75.7 L)
HULL THICKNESS: Bottom/side	.080"/.065" (2.0 mm/1.65 mm)	.080"/.065" (2.0 mm/1.65 mm)
2XB BOW: 2nd plate	.065" (1.65 mm)	.065" (1.65 mm)
SEATS: *	2	2
PEDESTALS/ SOCKETS:	2/6	2/5
BOW LIVE WELL:**	34 gal (128 L)	34 gal (128 L)
STEERING: CS console with no-feedback steering, removable windshield		
INSTRUMENTATION: speedometer, tachometer, voltmeter, fuel gauge, horn, blank		

* Driver's is stationary w/ slider, height adjust

** Aerated, bait systems, light (12" w × 14" h × 54" L / 30.48 cm × 35.56 cm × 137.16 m)

Celebrating a 65 year tradition of excellence

CLASSIC SERIES

165

SPECIAL PACKAGE PRICING

CLASSIC 165 CS AND TILLER

INCLUDES: Outboard Motor, Minn Kota SSPD
Trolling Motor, Humminbird Graph,
3 Deluxe Seats, and Trailer

SEE YOUR DEALER



CLASSIC 165 CS

Boat may be shown with optional equipment. See your dealer


STANDARD FEATURES

Rod Storage—Dual 7' Locking Compartments, Battery Storage (2 Batteries), Bow Livewell, Trolling—12V Bow Outlet, Stowable Running Lights, 2 Interior Courtesy Lights, Livewell Lights, 1 Manual Bilge Pump, Fire Extinguisher, Grab Handles, **Cup Holders**

OPTIONAL EQUIPMENT

Trolling Motor, Graph (Minn Kota, Humminbird, Lowrance), Vinyl Floor, Extra Seat and Pedestal, Mooring Covers

COLOR OPTIONS



Olympic White



Mica Black




Pacific Blue




Victory Red

■ STORAGE ■ ROD STORAGE ■ LIVEWELL ■ BATTERY STORAGE ● 12/24v OUTLET



165 CS



165 TILLER



CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE

NEW LUNKER II BOW ROD STORAGE LOCKER

LIVEWELL

LUNKER II BOW STORAGE

CONSOLE

LUNKER II BUILT IN FUEL TANK

does have holes drilled in edge due to transducer

"Most of the lakes I fish have a horsepower limit, so once I saw the new Lunker II with modest horsepower and a built-in fuel tank, I was hooked. Now I can navigate the lake, catch my limit, and make it back to the cabin without worrying about running low on fuel."

FISHERMAN 145 TILLER

FISHERMAN 160 CS

	LUNKER II CS	LUNKER II TILLER	FISHERMAN 160 CS	FISHERMAN 160	FISHERMAN 145 CS	FISHERMAN 145
LENGTH	16' 6" (5.0 m)	16' 6" (5.0 m)	16' 3" (4.9 m)	16' 3" (4.9 m)	14' 10" (4.5 m)	14' 10" (4.5 m)
WIDTH: Maximum beam	76" (1.93 m)	76" (1.93 m)	73" (1.85 m)	73" (1.85 m)	73" (1.85 m)	73" (1.85 m)
DEPTH: Maximum to floor	35" / 22" (.89 m / .56 m)	35" / 22" (.89 m / .56 m)	32" / 20" (.84 m / .55 m)	32" / 20" (.84 m / .55 m)	32" / 20" (.84 m / .55 m)	32" / 20" (.84 m / .55 m)
TRANSOM: Width/height	73" / 20" (1.85 m / .508 m)	73" / 20" (1.85 m / .508 m)	67" / 20" (1.7 m / .508 m)	67" / 20" (1.7 m / .508 m)	67" / 20" (1.7 m / .508 m)	67" / 20" (1.7 m / .508 m)
HORSEPOWER: Maximum	40 hp (30 kw)	40 hp (30 kw)	40 hp (30 kw)	25 hp (19 kw)	30 hp (19 kw)	25 hp (19 kw)
CAPACITY: Max Persons/Weight	5/1235 lbs (5/560 kg)	5/1235 lbs (5/560 kg)	5/1118 lbs (5/507 kg)	5/1118 lbs (5/507 kg)	4/925 lbs (4/420 kg)	4/925 lbs (4/420 kg)
WEIGHT:	740 lbs (336 kg)	705 lbs (320 kg)	622 lbs (282 kg)	600 lbs (272 kg)	602 lbs (273 kg)	580 lbs (263 kg)
FUEL TANK:	8 gal. (30.3 L)	8 gal. (30.3 L)	N/A	N/A	N/A	N/A
HULL THICKNESS: Bottom/side	.080" / .065" (2.0 mm / 1.65 mm)	.080" / .065" (2.0 mm / 1.65 mm)	.070" / .065" (1.78 mm / 1.65 mm)	.070" / .065" (1.78 mm / 1.65 mm)	.070" / .065" (1.78 mm / 1.65 mm)	.070" / .065" (1.78 mm / 1.65 mm)
SEATS: *	2	2	2	2	2	2
PEDESTALS / SOCKETS	2/4	2/4	2/4	2/4	2/4	2/4
SIDE LIVE WELL: **	13 gal. (49 L)	13 gal. (49 L)	13 gal. (49 L)	13 gal. (49 L)	13 gal. (49 L)	13 gal. (49 L)
STEERING:	No Feedback	N/A	Single cable SAFE-T	N/A	Single cable SAFE-T	N/A

no 2XB Hull in bow

* Driver's is stationary w/ slider, height adjust
** Aerated, bait systems (9" w x 13" h x 32" L / 22.86 cm x 33 cm x 81.28 cm)

Celebrating a 65 year tradition of excellence

LUNKER II & FISHERMAN

165

145 & 160

**BEST POINT
RESORT**
PEPSI POP • SANDWICHES PEPSI

SPECIAL PACKAGE PRICING

LUNKER II or FISHERMAN

INCLUDES: Outboard Motor,
Humminbird Graph,
2 Deluxe Seats, and Trailer

SEE YOUR DEALER

LUNKER II CS & LUNKER II TILLER

Boat may be shown with optional equipment. See your dealer


STANDARD FEATURES

Rod Storage-Center Floor Up To 7' (Fisherman), Rod Storage-Bow Floor Up To 7' (Lunker II), Livewell, Battery Storage (2 Batteries), 12 Volt Trolling Motor System, Electrical Circuit Breakers, Stowable Running Lights, 1 Manual Bilge Pump, Grab Handles

OPTIONAL EQUIPMENT

Windshield (Fisherman CS Models Only), Extra Seat And Pedestal, Graph (Humminbird, Lowrance), Vinyl Floor

COLOR OPTIONS



Olympic White




Mica Black

■ STORAGE ■ ROD STORAGE ■ LIVEWELL ■ BATTERY STORAGE ■ FUEL TANK ● 12V OUTLET

Lunker Series

Fisherman Series




165 CS


165 Tiller




160 CS



160




145 CS




145



CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE




V-16 (20'') V-14 T14V T12V



QT 185 CO 17 QT 17 QT 15




NEW SPLIT SEAT [V16 & V14]




DEEP V DESIGN

COLOR OPTIONS (V14 & V16)



Olympic White



Mica Black



SPECIFICATIONS: Canoes

	QT 185	CO 17	QT 17	QT 15
LENGTH	18'5" (5.61 m)	17' (5.18 m)	17' (5.18 m)	15' (4.57 m)
WIDTH: Maximum beam	37" (.94 m)	37" (.94 m)	36" (.91 m)	36" (.91 m)
DEPTH: Mid Ship	13" (.33 m)	13" (.33 m)	13" (.33 m)	12" (.30 m)
TRANSOM: Height	N/A	15" (.51 m)	N/A	N/A
HORSEPOWER: Maximum	N/A	4 hp (2.98 kw)	N/A	N/A
CAPACITY: Max Persons	4/800 lbs (4/363 kg)	4/805 lbs (4/364 kg)	4/750 lbs (4/340 kg)	3/652 lbs (3/296 kg)
WEIGHT	67 lbs (32.2 kg)	83 lbs (36.3 kg)	64 lbs (29 kg)	56 lbs (25.4 kg)
HULL THICKNESS: Bottom	0.040" (1 mm)	0.040" (1 mm)	0.040" (1 mm)	0.040" (1 mm)
KEEL TYPE - Cruising	0.625" (1.6 mm)	0.625" (1.6 mm)	0.625" (1.6 mm)	0.625" (1.6 mm)
STEM GAUGE	.090 (2.3 mm)	.090 (2.3 mm)	.090 (2.3 mm)	.090 (2.3 mm)
NUMBER OF RIBS	6	5	5	3
CURVED THWART	Optional	Optional	Standard	Standard
BENCH TYPE - Forward/Aft	1/1	1/1	1/1	1/1

SPECIFICATIONS: Vs and Ts

	V-16 (20'')	V-14 (20'')	V-14 (15'')	T14V	T12V
LENGTH	16'7" (5 m)	14'3" (4.3 m)	14'3" (4.3 m)	14' (4.2 m)	12' (3.7 m)
WIDTH: Maximum beam	70" (1.78 m)	68" (1.72 m)	68" (1.72 m)	61" (1.54 m)	60" (1.52 m)
BOW HEIGHT	30" (.76 m)	30" (.75 m)	30" (.75 m)	26" (.65 m)	25" (.64 m)
TRANSOM: Width/height	62"/20" (1.58 m/.51 m)	62"/20" (1.58 m/.51 m)	62"/15" (1.58 m/.38 m)	60"/15" (1.52 m/.38 m)	60"/15" (1.52 m/.38 m)
HORSEPOWER: Maximum	25 hp (19 kw)	20 hp (15 kw)	20 hp (15 kw)	15 hp (11 kw)	10 hp (7 kw)
CAPACITY: Max Persons	5/1380 lbs (5/626 kg)	5/1195 lbs (5/542 kg)	5/1015 lbs (5/460 kg)	4/825 lbs (5/374 kg)	3/650 lbs (5/297 kg)
WEIGHT	285 lbs (129 kg)	235 lbs (107 kg)	230 lbs (104 kg)	180 lbs (82 kg)	160 lbs (72.7 kg)
FUEL TANK	N/A	N/A	N/A	N/A	N/A
HULL THICKNESS: Bottom/Side	.065"/.065" (1.65 mm/1.65 mm)	.065"/.065" (1.65 mm/1.65 mm)	.065"/.065" (1.65 mm/1.65 mm)	.060"/.050" (1.52 mm/1.27 mm)	.060"/.050" (1.52 mm/1.27 mm)
2XB BOW - 2nd plate	N/A	N/A	N/A	N/A	N/A
2XB AFT BOTTOM - 2nd plate	N/A	N/A	N/A	N/A	N/A
SPLIT AFT SEATS	Split Aft	Split Aft	Split Aft	N/A	N/A
BENCH / BOW *	2/1	2/1	2/1	3/0	3/0


* OXFORD WHITE paint w/ DOVE GRAY interior

Celebrating a 65 year tradition of excellence

THE ALUMACRAFT DIFFERENCE


BASS / CRAPPIE / MV SERIES / JON BOATS

Let's face it, things can get pretty confusing when you shop for a boat. Manufacturers love to talk about all their features. But what most customers really want to know is this: What do your boats have that their boats don't? So here's the straight truth about what you can only get with an Alumacraft.



1. FULL-LENGTH ONE-PIECE OVERSIZED RIBS ON OUR RIVETED BOATS

What it means to you: strength and dependability. Our ribs are 12" on center on our all-welded boats, 15" on center on our riveted boats. The competition uses fewer ribs and spaces them wider, which is little like building a house out of code. Sure, it costs a little more to build our boats this way, but we want yours to last.



2. ONE-PIECE HULL CONSTRUCTION

What it means to you: no metal fatigue and a quieter ride. The competition uses as many as three pieces for their hulls. All that welding creates more margin for error and affects the quality of your ride. Combine our one-piece hull with our oversized ribs, and you know you're getting a superior boat that's both quiet and built to last.




3. MORE KEEL BREAKS

What it means to you: a stronger hull. A keel break is built-in or pressed ribs in your hull. At Alumacraft, we build our keels with more pressed ribs than the competition—because more "breaks" means a stronger hull. Combine Alumacraft's seven keel breaks on welded products with our oversized ribs, stringers and one-piece hull construction, and you've got the strongest hull for your money. Period.



4. ALUMINUM TRANSDOM CONSTRUCTION

What it means to you: Our all-welded jons boast an all-aluminum transom featuring heavy welded box channels with .125 aluminum on both sides. Sure, this isn't something you can see from the outside, but when you ride an Alumacraft, you can rest assured that your motor is sitting on what we believe to be the strongest transom in the business.



5. WELDED FLOORS

What it means to you: a quieter, finished floor. The other guys use rivets on their floors; we weld ours in. The result is not only a quieter floor, but also the peace of mind that you won't pop rivets when you're in the rough stuff. Plus, unlike our competitors, Alumacraft gives you an all-welded jon boat (with floor) that also includes aluminum sides. That's the whole package—and better value.



6. RIVETED BOAT TRANSOMS

What it means to you: a more reliable boat. The outside of a riveted jon boat transom may look the same from boat to boat, but the real difference is on the inside. Some of the competition will only use a 6" board from the top. At Alumacraft, we support our transoms the full height—giving you the quality and value you expect for your hard-earned money.

CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE



NEW CONSOLE



NEW LIVEWELL - PRO



DUAL LOCKABLE BOW STORAGE - PRO



BOW STORAGE - PF



UNDER SEAT STORAGE - PF

"I got a PF 175 because I wanted a boat that would work hard so I could play hard. It's small enough to get me into the tightest timber, but big enough to store all my gear. You've got to love something that makes having fun this easy."



PF 175

	PRO 175	PF 175
LENGTH	17' 5" (5.31 m)	17' 5" (5.31 m)
WIDTH: Maximum beam	88"/56" (26.8 m/17.7 m)	88"/56" (26.8 m/17.1 m)
SIDE HEIGHT	23" (7.01 m)	23" (7.01 m)
TRANSOM: Width/height	88"/21" (26.8 m/6.4 m)	88"/21" (26.8 m/6.4 m)
HORSEPOWER: Maximum	90 hp (67 kw)	90 hp (67 kw)
CAPACITY: Max Persons	4/1200 lbs (4/544 kg)	4/1195 lbs (4/542 kg)
WEIGHT	1000 lbs (453.59 kg)	1050 lbs (476.27 kg)
FUEL TANK	21 gal (79.5 L)	21 gal (79.5 L)
HULL THICKNESS: Bottom/side	.102"/.102" (2.6 mm/2.6 mm)	.102"/.102" (2.6 mm/2.6 mm)
SEATS *	5	4
PEDESTALS/ SOCKETS	2/2	2/3
LIVE WELLS: Bow **	20 gal. each (75.71 L)	20 gal. each (75.71 L)
LIVE WELLS: Aft **	20 gal. each (75.71 L)	20 gal. each (75.71 L)
STEERING:	No Feedback	No Feedback
CONSOLE: Fiberglass w/ windscreen		
INSTRUMENTATION: speedometer, tachometer, fuel gauge		

* 3 deluxe bucket seats and 2 pedestal seats (PRO); 2 deluxe bucket seats and 2 pedestal seats (PF)

** Aerated, remote drain (PRO); aerated (PF)

Celebrating a 65 year tradition of excellence

PRO AND PF PACKAGES

PRO 175 & PF 175

SPECIAL PACKAGE PRICING

PRO 175 or PF 175

INCLUDES: Outboard, Minn Kota Edge 45 Trolling Motor, Humminbird Graph, 5 Dlx Seats (Pro), 4 Dlx Seats (PF), and Trailer

SEE YOUR DEALER



PRO 175

Boat may be shown with optional equipment. See your dealer

STANDARD FEATURES

Lockable Rod Storage (Pro 175 dual-bow, PF 175 side), Dual Livewells, Saltwater Resistant System, Nav And Trim Switch On Bow, 12V Power Point, 12/24 Volt Bow Outlet, Stowable Running Lights, Interior Courtesy Light, Manual Bilge Pump

OPTIONAL EQUIPMENT

Trolling Motor (Minn Kota), Graph (Lowrance Or Humminbird)

COLOR OPTIONS




Mica Black



Gray



Pacific Blue



Victory Red

■ STORAGE ■ ROD STORAGE ■ LIVEWELL ■ BATTERY STORAGE ● 12/24v OUTLET



PRO 175



PF 175



CELEBRATING A
65 YEAR
TRADITION OF EXCELLENCE

"I got a Crappie Deluxe because I think life is about two things and two things only: fishing and family. This is a boat we can take anywhere, any time. It's easy to haul around, comfortable to be on, and totally hassle-free."




CRAPPIE DELUXE LIVEWELL




MV TEX CONSOLE




MV TEX LIVEWELL



GRAPH



LOCKABLE BOW STORAGE



CRAPPIE JON



CRAPPIE DELUXE

	MV Tex Special	Crappie Deluxe	Crappie Jon
LENGTH	16' 0" (4.88 m)	16' 0" (4.88 m)	14' 0" (4.27 m)
WIDTH: Beam/bottom	74"/50" (22.6 m/15.2 m)	70"/48" (21.3 m/14.6 m)	64"/42" (19.5 m/12.8 m)
SIDE HEIGHT	21" (6.4 m)	21" (6.4 m)	20" (6.1 m)
TRANSOM: Width/height	69"/21" (21.0 m/6.4 m)	68"/20" (20.7 m/6.1 m)	62"/15" (18.9 m/4.6 m)
HORSEPOWER: Maximum	60 hp (45 kw)	30 hp (22 kw)	15 hp (11 kw)
CAPACITY: Persons/lbs	4/1010 lbs (4/458 kg)	2/745 lbs (2/338 kg)	2/550 lbs (2/249 kg)
WEIGHT: lbs	675 lbs (307 kg)	520 lbs (236 kg)	330 lbs (150 kg)
THICKNESS: Bottom/sides	0.102" (2.6 mm)	0.072" (1.8 mm)	0.063" (1.6 mm)
SEATS:	4	2	2
LIVEWELL: *	20 gal. (75.71 L)	10 gal. (37.85 L)	5 gal. (18.93 L)
STEERING:	No Feedback	No Feedback	No Feedback
CONSOLE: Fiberglass w/ windscreen			
INSTRUMENTATION: speedometer, tachometer, voltmeter			

* Aerated (MV Tex Special); Aerated w/ seat cushion (Crappie Deluxe); Livewell box (Crappie Jon)

Celebrating a 65 year tradition of excellence

MV TEX & CRAPPIES

MV TEX SPECIAL, CRAPPIE DELUXE & CRAPPIE JON

SPECIAL PACKAGE PRICING

MV TEX SPECIAL

INCLUDES: Outboard, Minn Kota Edge 45
Trolling Motor, Humminbird Graph,
4 Deluxe Seats, and Trailer

SEE YOUR DEALER



MV TEX SPECIAL

Boat may be shown with optional equipment. See your dealer


STANDARD FEATURES

Welded-In Aluminum Floor And Decks, All-Aluminum Transom (Mv Tex Special), 2 Compartments (Mv Tex Special), 1 Compartment (Crappie Jon), Livewell, 12 Volt Harness Trolling (Mv Tex Special), Bow Bracket Trolling (Crappie), Stowable Running Lights And Interior Courtesy Light (Mv Tex Special), Stowable Running Lights (Crappie Deluxe), Bilge Pump (Mv Tex Special)


OPTIONAL EQUIPMENT

Trolling Motor (Minn Kota), Graph (Lowrance or Humminbird), Spray-In-Liner (Mv Tex Special)

COLOR OPTIONS




Mica Black



Gray
(Crappie Std.)



Pacific Blue



Victory Red

■ STORAGE ■ LIVEWELL ■ BATTERY STORAGE ● 12/24v OUTLET



MV TEX SPECIAL



CRAPPIE DELUXE




CRAPPIE JON




CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE

"I got an 18' All-Weld Jon from Alumacraft because I knew it would be a totally solid boat. It's not easy to find something that's totally no-nonsense and affordable but also gives you great performance and value. But that's exactly what you get with this boat."




SIDE CONSOLE



LIVEWELL



NEW HULL SIDE BREAK



LIVEWELL (CC)



CENTER CONSOLE



MV 1860 CC



MV 1860 SC

Celebrating a 65 year tradition of excellence


20'-18' ALL WELDS



MV 2072 AWFF

Boat may be shown with optional equipment. See your dealer

■ STORAGE ■ ROD STORAGE ■ LIVELWELL ■ BATTERY STORAGE ● 12/24v OUTLET



MV 2072 AW

MV 2072 AW SC

MV 2072 AW FF

MV 2072 AW CC

MV 2072 AW TUNNEL FF

MV 1860 AW


MV 1860AW SC

MV 1860 AW CC

VB 1860 AW TUNNEL SC

VB 1860 AW TUNNEL

CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE



CENTER CONSOLE




LIVEWELL - MV 1756 CC



BOW FISH CHAIR



LOCKABLE STORAGE



NEW HULL SIDE BREAK



MV 1756 CC



WATERFOWLER 16



Shown with optional camo paint.

Celebrating a 65 year tradition of excellence


17' 16' 15' ALL WELDS



MV 1650 SC

Boat may be shown with optional equipment. See your dealer

■ STORAGE ■ ROD STORAGE ■ LIVEWELL ■ BATTERY STORAGE ● 12/24v OUTLET



MV 1756

MV 1756 SC

MV 1756 CC

MV 1650

MV 1650 SC

MV 1650 CC

WATERFOWLER 16

MV 1546 AW

MV 1546 DD

MV 1546 DD TUNNEL

CELEBRATING A
65 YEAR
 TRADITION OF EXCELLENCE

"I love my modified V-hull Alumacraft Riveted Jon for its toughness, simplicity, durability and performance. If you're looking for 'no ordinary jon,' it makes sense to go with a company that's been making high-quality riveted boats for over 60 years."



STORAGE LOCKER



SPLIT SEAT



OPTIONAL SIDE CONSOLE



OPTIONAL LIVEWELL



TROLLING MOTOR BRACKET



ALL YAMAHA FOUR STROKES EXCEED FEDERAL EPA 2006 EMISSION REQUIREMENTS. THE NEW F60, F75 AND F90 HORSEMODELS HAVE EARNED A CALIFORNIA C.A.R.B. THREE-STAR RATING.

■ STORAGE ■ LIVEWELL



MV 1648 SS



MV 1648 (15&20)



MV 1448 (15&20)



1648 NCS


Celebrating a 65 year tradition of excellence

RIVETED JONS



MV 1648 SS

Boat may be shown with optional equipment. See your dealer



1648 (15 & 20)

1448 (15 & 20)

1542

1442

1442 NCS

1442 LW

1436

1436 LT






1236

1036

	MV 2072 ANI FF	MV 2072 ANI TUNNEL FF	MV 2072 ANI TUNNEL CC	MV 2072 ANI SC	MV 2072 ANI	MV 2072 ANI TUNNEL	MV 1860 ANI SPECIAL	VB 1860 ANI SPECIAL TUNNEL	MV 1860 ANI CC	VB 1860 ANI TUNNEL CC	MV 1860 ANI SC	VB 1860 ANI TUNNEL SC	MV 1860 ANI	VB 1860 ANI TUNNEL	MV 1736 ANI CC
LENGTH	20'0"	20'0"	20'0"	20'0"	20'0"	20'0"	18'0"	18'0"	18'0"	18'0"	18'0"	18'0"	18'0"	18'0"	17'0"
BOTTOM WIDTH	72"	72"	72"	72"	72"	72"	60"	60"	60"	60"	60"	60"	60"	60"	56"
BEAM SIDE HEIGHT	94"/27"	94"/27"	94"/27"	94"/27"	94"/27"	94"/27"	86"/25"	86"/25"	86"/25"	86"/25"	86"/25"	86"/25"	86"/25"	86"/25"	83"/24"
TRANSOM HEIGHT (All-aluminum)	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"
MAXIMUM HORSEPOWER	130 hp	130 hp	130 hp	115 hp	115 hp	60 hp	60 hp	115 hp	115 hp	115 hp	90 hp	90 hp	90 hp	50 hp	50 hp
HORSEPOWER (Optional side Console)	—	—	—	—	90 hp ¹	90 hp ¹	—	—	—	—	—	—	75 hp	75 hp	—
FUEL TANK	21 gal.	21 gal.	21 gal.	21 gal.	—	—	21 gal.	21 gal.	21 gal.	21 gal.	21 gal.	21 gal.	—	—	21 gal.
APPROXIMATE WEIGHT	1200 lbs.	1200 lbs.	1200 lbs.	1100 lbs.	850 lbs.	850 lbs.	1050 lbs.	1050 lbs.	905 lbs.	905 lbs.	875 lbs.	875 lbs.	680 lbs.	680 lbs.	860 lbs.
CAPACITY	8/2100 lbs	8/2100 lbs	8/2100 lbs.	8/2100 lbs.	8/2100 lbs.	8/2100 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	6/1600 lbs	5/1300 lbs
HULL GAUGE	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"
HULL TYPE	Modified-V	MV Tunnel	MV Tunnel	Modified-V	Modified-V	MV tunnel	Modified-V	Flat-V tunnel	Modified-V	Flat-V tunnel	Modified-V	Flat-V tunnel	Modified-V	Modified-V	Modified-V
NUMBER OF RIBS	L	L	L	L	15	15	L	L	L	L	L	L	13	13	L
SIDE CONSOLE	—	—	—	✓	Opt.	Opt.	—	—	—	—	✓	✓	Opt.	Opt.	—
CENTER CONSOLE	✓+6RH	✓+6RH	✓+6RH	—	—	—	✓+6RH	✓+6RH	✓+6RH	✓+6RH	—	—	—	—	✓
WINDSHIELD	✓	✓	✓	✓	Opt.	Opt.	✓	✓	✓	✓	✓	✓	Opt.	Opt.	✓
INSTRUMENTATION	✓ S, T, F	✓ S, T, F	✓ S, T, F	✓ S, T, F	—	—	✓ S, T, F	✓ S, T, F	✓ S, T, F	✓ S, T, F	✓ S, T, F	✓ S, T, F	—	—	✓ S, T, F
LIVWELL	✓	✓	✓	✓	—	—	✓	✓	✓	✓	✓	✓	—	—	✓
STORAGE COMPARTMENTS	2	2	2	3 + rod	2	2	2	2	2	2	3 + rod	3 + rod	2	2	2
DRY STORAGE COMPARTMENTS	—	—	—	1	—	—	—	—	—	—	1	1	—	—	—
GUN BOX	—	—	—	—	Opt.	Opt.	—	—	—	—	—	—	Opt.	Opt.	—
SEATS	FF, Cons.	FF, Cons.	Cons.	2	—	—	Cons.	Cons.	Cons.	Cons.	2	2	—	—	—
FISHING SEATS	2	2	2	2	Opt.	Opt.	2	2	2	2	2	2	Opt.	Opt.	2
SEAT PEDESTAL BASES	2 pin	2 pin	1 pin, 1L	2 pin	Opt.	Opt.	1 pin, 1L	1 pin, 1L	1 pin, 1L	1 pin, 1L	2 pin	2 pin	Opt.	Opt.	1 pin, 1L
COOLER	✓	✓	—	—	—	—	—	—	—	—	—	—	—	—	—
FLOOR	✓	✓	✓	✓	Opt.	Opt.	✓	✓	✓	✓	✓	✓	Opt.	Opt.	✓
DROP DECK	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
TROLLING MOTOR, GRAPH	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
TRI-MOTOR HARNESS	✓w/TT	✓w/TT	✓w/TT	✓w/TT	—	—	✓w/TT	✓w/TT	✓w/TT	✓w/TT	✓w/TT	✓w/TT	—	—	✓
LIGHTS	✓	✓	✓	✓	Opt. ¹	Opt. ¹	✓	✓	✓	✓	✓	✓	Opt. ¹	Opt. ¹	✓
POWER POINTS	1	1	1	1	—	—	1	1	1	1	1	1	—	—	1
BILGE PUMP	✓	✓	✓	✓	—	—	✓	✓	✓	✓	✓	✓	—	—	✓
SPRAY-IN FLOOR LINER	Opt.	Opt.	Opt.	Opt.	—	—	✓	✓	Opt.	Opt.	Opt.	Opt.	—	—	Opt.
SPONGONS	—	Opt.	Opt.	—	—	Opt.	—	Opt.	—	Opt.	—	—	—	Opt.	—
PAINT COLOR	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	White	White	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki
CAMO PAINT	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	NA	NA	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.

¹ WITH OPTIONAL FLOOR PACKAGE INSTALLED AT FACTORY ONLY

	MV 1648	MV 1648 NCS	MV 1448	1648	1648 NCS	1448	1542	1442	1442 LW	1442 NCS	1436	1436 LT	1236	1036
LENGTH	16.0"	16.0"	14.0"	16.0"	16.0"	14.0"	15.0"	14.0"	14.0"	14.0"	14.0"	14.0"	12.0"	10.0"
BOTTOM WIDTH	48"	48"	48"	48"	48"	48"	48"	48"	48"	48"	48"	48"	48"	48"
BEAM SIDE HEIGHT	70"/21"	70"/21"	70"/21"	70"/21"	70"/21"	70"/21"	62"/20"	62"/20"	62"/20"	62"/20"	55"/19"	55"/19"	55"/19"	55"/19"
TRANSOM HEIGHT (All-aluminum)	15"/20"	15"/20"	15"/20"	15"/20"	15"/20"	15"/20"	15"	15"	15"	15"	15"	15"	15"	15"
MAXIMUM HORSEPOWER	30 hp	35 hp	25 hp	30 hp	30 hp	25 hp	25 hp	25 hp	25 hp	25 hp	15 hp	15 hp	15 hp	3 hp
APPROXIMATE WEIGHT	280 lbs	310 lbs	250 lbs	285 lbs	260 lbs	260 lbs	210 lbs	190 lbs	210 lbs	230 lbs	180 lbs	135 lbs	125 lbs	105 lbs
CAPACITY	5/1010 lbs	5/1010 lbs	5/585 lbs	5/1010 lbs	5/1010 lbs	5/585 lbs	4/775 lbs	3/755 lbs	3/755 lbs	3/755 lbs	3/605 lbs	3/625 lbs	3/540 lbs	3/365 lbs
HULL GAUGE	.070"	.070"	.070"	.070"	.070"	.070"	.063"	.063"	.063"	.063"	.058"	.053"	.053"	.053"
HULL TYPE	Modified-V	Modified-V	Modified-V	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom	Flatbottom
NUMBER OF RIBS	9	9	7	9	9	7	8	7	7	7	7	6	5	2
SIDE STEERING	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	—	—	—	—
LIVWELL	Opt.	—	Opt.	Opt.	—	Opt.	—	—	✓	—	Opt.	Opt. box	—	—
CENETR BENCH - BENCH SEAT	✓w/storage	—	✓w/storage	✓w/storage	—	✓w/storage	✓	✓	✓	—	✓w/storage	✓	✓	✓
CAMO SEAT	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
LIGHT & TROLLING MOTOR BRACKET	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
COLOR	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green	Olive Drab Green



MV 1648 SS

MV 1648 (15&20)

MV 1448 (15&20)

1648 NCS

1648 (15 & 20)

1448 (15 & 20)

1542

1442

1442 NCS

1442 LW

1436

1436 LT

1236

1036

VB 1735 AW TUNNEL CC	MV 1735 AW SC	VB 1735 AW TUNNEL SC	MV 1735 AW	VB 1735 AW TUNNEL	MV 1630 AW CC	VB 1630 AW TUNNEL CC	MV 1630 AW SC	VB 1630 AW SC	MV 1630 AW	VB 1630 AW TUNNEL	WATERFOWLER 16	MV 1546 AW DD	MV 1546 AW DD TUNNEL	MV 1546 AW
17'0"	17'0"	17'0"	17'0"	17'0"	18'0"	16'0"	16'0"	16'0"	16'0"	16'0"	16'0"	16'0"	15'0"	15'0"
56"	56"	56"	56"	56"	50"	50"	50"	50"	50"	50"	50"	46"	46"	46"
83"/24"	83"/24"	83"/24"	83"/24"	83"/24"	74"/22"	74"/22"	74"/22"	74"/22"	74"/22"	74"/22"	65"/20"	65"/20"	65"/20"	65"/20"
21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	21"	15"	15"	15"
75 hp	75 hp	75 hp	50 hp	50 hp	60 hp	60 hp	60 hp	60 hp	60 hp	60 hp	40 hp	25 hp	25 hp	25 hp
—	—	—	75 hp	75 hp	—	—	—	—	60	60 hp	—	25 hp	25 hp	25 hp
21 gal.	21 gal.	21 gal.	—	—	—	—	—	—	—	—	—	—	—	—
860 lbs.	830 lbs.	830 lbs.	600 lbs.	600 lbs.	690 lbs.	690 lbs.	680 lbs.	680 lbs.	485 lbs.	485 lbs.	525 lbs.	340 lbs.	340 lbs.	340 lbs.
5/1300 lbs	5/1300 lbs	5/1300 lbs	5/1300 lbs	5/1300 lbs	5/1100 lbs	5/1100 lbs	5/1100 lbs	5/1100 lbs	5/1100 lbs	5/1100 lbs	5/1100 lbs	3/719 lbs	3/719 lbs	3/719 lbs
.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.102"	.080"	.080"	.080"
Flat-V tunnel	Modified-V	Flat-V tunnel	Modified-V	Modified-V	Flat-V tunnel	Modified-V	Modified-V	Flat-V tunnel	Modified-V	Flat-V tunnel	Modified-V	Modified-V	Modified-V tunnel	Modified-V
L	L	L	13	13	L	L	L	L	11	11	L	11	11	11
—	✓	✓	Opt.	Opt.	✓	—	✓	✓	Opt.	Opt.	—	Opt.	Opt.	Opt.
✓	—	—	—	—	✓	✓	—	—	—	—	—	—	—	—
✓	✓	✓	Opt.	Opt.	✓	✓	✓	✓	Opt.	Opt.	—	—	—	—
✓ S, T, F	✓ S, T, F	✓ S, T, F	—	—	✓ S, T, V	✓ S, T, V	✓ S, T, V	✓ S, T, V	—	—	—	—	—	—
✓	✓	✓	—	—	✓	✓	✓	✓	—	—	—	—	—	—
2	3 + rod	3 + rod	2	2	2	2	3	3	2	2	1	—	—	—
—	1	1	—	—	—	—	1	1	—	—	—	—	—	—
—	—	—	Opt.	Opt.	—	—	—	—	Opt.	Opt.	1	Opt.	Opt.	Opt.
—	2	2	—	—	—	—	2	2	—	—	—	—	—	—
2	2	2	Opt.	Opt.	2	2	2	2	—	—	—	—	—	—
1 pin, 1L	2 pin	2 pin	Opt.	Opt.	1 pin, 1L	1 pin, 1L	2 pin	2 pin	Opt.	Opt.	1 pin	1 pin	1 pin	Opt.
—	—	—	—	—	—	—	—	—	Opt.	Opt.	✓	Opt.	Opt.	Opt.
✓	✓	✓	Opt.	Opt.	✓	✓	✓	✓	Opt.	Opt.	✓	✓	✓	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
✓	✓	✓	—	—	✓ 12V	✓ 12V	✓ 12V	✓ 12V	—	—	✓ 12V	—	—	—
✓	✓	✓	Opt. ¹	Opt. ¹	✓	✓	✓	✓	Opt.	Opt.	✓	—	—	—
1	1	1	—	—	1	1	1	1	—	—	1	—	—	—
✓	✓	✓	—	—	✓	✓	✓	✓	—	—	✓	—	—	—
Opt.	Opt.	Opt.	—	—	Opt.	Opt.	Opt.	Opt.	—	—	—	—	—	—
Opt.	—	—	—	Opt.	—	Opt.	—	—	—	Opt.	—	—	—	—
Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki	Khaki
Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.

¹ WITH OPTIONAL FLOOR PACKAGE INSTALLED AT FACTORY ONLY



ALL YAMAHA FOUR STROKES EXCEED FEDERAL EPA 2006 EMISSION REQUIREMENTS. THE NEW F60, F75 AND F90 HORSEMODELS HAVE EARNED A CALIFORNIA C.A.R.B. THREE-STAR RATING.


PHOTOS MAY SHOW OPTIONAL EQUIPMENT. INFORMATION IS SUBJECT TO CHANGE. SEE YOUR DEALER FOR CURRENT SPECIFICATIONS AND INFORMATION.

JON BOAT

SPECIFICATIONS



MV 2072 AW MV 2072 AW SC MV 2072 AW FF MV 2072 AW CC MV 2072 AW TUNNEL FF MV 1860 AW MV 1860 AW SC



MV 1860 AW CC VB 1860 AW TUNNEL SC VB 1860 AW TUNNEL MV 1756 MV 1756 SC MV 1756 CC MV 1650 MV 1650 SC MV 1650 CC WATERFOWLER 16 MV 1546 AW MV 1546 DD MV 546 DD TUNNEL

BOAT OPTIONS



MINN KOTA TROLLING MOTORS



HUMMINBIRD / LOWRANCE GRAPHS



HYDRAULIC STEERING & TILT WHEEL



AIR RIDE PEDESTALS



HIGH RISE BIMINI TOP



BIMINI TOP & ENCLOSURE


(ONLY FOR USE WHEN BOAT IS AT REST, ENGINE OFF)



VINYL FLOOR




BOW ROD STORAGE (TROPHY'S)



STEREO'S - DEALER INSTALLED




BOW CUSHIONS



PRO SEAT



SPRAY-IN LINER



JON BOAT SIDE CONSOLE



LIVWELL OPTIONS (JONS)



FLOOR & SIDES (ALL WELDS)



DOOR LOCKS



CAMO PAINT



TROLLING MOTOR BRACKET



SPONSONS